

RTCxx: Thin Wall C-Taps

**Features:**

- Used for tapping, splicing, and pigtailling of copper ground wires
- Color coded for easy crimp die selection
- Suitable for use in direct burial connections

Construction:

- High conductivity wrought copper

Design Criteria:

- Rated to UL467 for grounding and bonding applications

RTCxx: Thin Wall C-Taps

| Part # | Conductor Size Range | | # of Ribs | Dimensions | | | | Strip Length | Crimp Die Color Code |
|--------|----------------------|-------|-----------|------------|-------|-------|-------|--------------|----------------------|
| | Run | Tap | | B | C | D | T | | |
| RTC4 | 6 | 6-8 | 1 | 0.39" | 0.28" | 1.17" | 0.07" | 1-1/4" | Brown |
| | 6,4 | 8-12 | | | | | | | |
| RTC5 | 6,4 | 4-6 | 1 | 0.45" | 0.26" | 1.17" | 0.07" | 1-1/4" | Green |
| | 3 | 6-12 | | | | | | | |
| RTC6 | 4 | 4 | 1 | 0.49" | 0.30" | 1.17" | 0.07" | 1-1/4" | Pink |
| | 3 | 4-6 | | | | | | | |
| | 2 | 6-12 | | | | | | | |
| RTC7 | 3 | 3-4 | 2 | 0.53" | 0.31" | 1.75" | 0.07" | 2" | Black |
| | 2 | 4-6 | | | | | | | |
| | 1 | 4-12 | | | | | | | |
| RTC8 | 2 | 2-4 | 2 | 0.61" | 0.41" | 1.75" | 0.09" | 2" | Orange |
| | 1 | 3-4 | | | | | | | |
| | 1/0 | 4-12 | | | | | | | |
| RTC9 | 1 | 1-2 | 2 | 0.69" | 0.42" | 1.75" | 0.09" | 2" | Purple |
| | 1/0 | 2-3 | | | | | | | |
| | 2/0 | 3-12 | | | | | | | |
| RTC10 | 1/0 | 1/0-1 | 2 | 0.81" | 0.46" | 1.75" | 0.09" | 2" | Yellow |
| | 2/0 | 1-2 | | | | | | | |
| | 3/0 | 2-12 | | | | | | | |

