

	PARTS LIST									
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.				
1	1	BP9625-12	V-BRACE REAR TOWER LEG BRACKET	9 5/8 in	12.62	12.62				
2	1	BRKW-VBSM	V-BRACE FRONT TOWER LEG BRACKET WELDMENT		16.76	16.76				
3	2	L252525-8	ANGLE BRACE (FIELD MODIFICATION REQUIRED)	96 in	34.52	69.04				
4	4	BP6875-10	BENT PLATE BRACKET	10 in	3.82	15.30				
5	2	AL-333	CLIP ANGLE	3 in	1.25	2.50				
6	4	G58R-18	5/8" x 18" THREADED ROD (HDG.)		1.57	6.27				
7	4	G58R-10	5/8" x 10" THREADED ROD (HDG.)		0.87	3.48				
8	1	A582114	5/8" x 2-1/4" HDG A325 HEX BOLT	2 1/4 in	0.31	0.31				
9	2	A5802	5/8" x 2" HDG A325 HEX BOLT		0.27	0.54				
10	2	A58134	5/8" X 1-3/4" HDG A325 BOLT	1 3/4 in	0.27	0.54				
11	21	G58LW	5/8" HDG LOCKWASHER		0.03	0.55				
12	21	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	2.73				
		•			TOTAL WT. #	130.08				




DETAIL A




DETAIL B


	TOLERANCE NOTES	DESCRIPTION						
	TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES ( $\pm 0.030$ ") DRILLED AND GAS CUT HOLES ( $\pm 0.030$ ") - NO CONING OF HOLES LASER CUT EDGES AND HOLES ( $\pm 0.010$ ") - NO CONING OF HOLES BENDS AND ANGLES ARE $\pm 1/2$ DEGREE ALL OTHER MACHINING ( $\pm 0.030$ ") ALL OTHER ASSEMBLY ( $\pm 0.060$ ")	VZW SMART SECTOR FRAME REINFORCEMENT KIT						
		CPD NO.		DRAWN	BY	ENG. APP	ROVA	
				CSL	3/25/2020		5/ <sup>-</sup>	
		CLASS	SUB	DRAWIN	G USAGE	CHECKED	BY	
	THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.	87	02		SHOP	BMC	5/ <sup>-</sup>	



Valmont Site Pro 1 Lori.Espinosa@valmont.com (631) 715-3045 www.sitepro1.com








	-					
TOLERANCE NOTES	DESC					
TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES (± 0.030") DRILLED AND GAS CUT HOLES (± 0.030") - NO CONING OF HOLES LASER CUT EDGES AND HOLES (± 0.010") - NO CONING OF HOLES BENDS AND ANGLES ARE ± 1/2 DEGREE	VZW SMART SECTOR FRAME REINFORCEMENT KIT					
ALL OTHER MACHINING (± 0.030")	CPD NO.		DRAWN BY		ENG. APPRO	כ
ALL OTHER ASSEMBLY (± 0.060")			CSL	3/25/2020		5
PROPRIETARY NOTE: THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT	CLASS	SUB	DRAWIN	G USAGE	CHECKED B	Y
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STDICTLY PROLIDED.	87	02		SHOP	BMC	Ę

## **VERTICAL POSITION**





TOLERANCE NOTES	DESCRIPTION						
TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES (± 0.030") DRILLED AND GAS CUT HOLES (± 0.030") - NO CONING OF HOLES LASER CUT EDGES AND HOLES (± 0.010") - NO CONING OF HOLES BENDS AND ANGLES ARE ± 1/2 DEGREE		VZW SMART SECTOR FRAME REINFORCEMENT KIT					
ALL OTHER MACHINING (± 0.030") ALL OTHER ASSEMBLY (± 0.060")	CPD NO.		DRAWN BY		ENG. APPROV		
			CSL	3/25/2020		5	
OPRIETARY NOTE: E DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT	CLAS	S SUB	DRAWIN	G USAGE	CHECKED	) BY	
INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALIMONT INDUSTRIES IS STRICTLY PROHIBITED.	87	02		SHOP	BMC	5	

## HORIZONTAL POSITION

